

# The Berks County Fair

## Light Farm Stock Rules 7500-9500

**\*\*\*\* Any decision made the day of will supersede these posted rules.\*\*\*\***

**Hook fee will be \$20/hook, with a yearly \$10 insurance fee for each driver.**

- 1) 18.4-38 max tire size for all classes, NO CUT TIRES, all tires must be pneumatic rubber tires.
- 2) 20" hitch height, minimum 18" behind centerline of rear axle, hitch holes must be minimum 3"x3.75" and minimum of 1/2" thick, and hitch deemed unsafe will not be allowed to pull. NO FLOATING HITCHES & NO CLEVISES
- 3) 7500-9500 will run at 6mph Fenders required for 1965 and newer tractors
- 4) Naturally aspirated tractors only, no turbos. Detroit diesel 2 strokes may run with a factory blower.
- 5) RPM's limited to 3,000 rpm's
- 6) Gas, diesel, and LP only permissible fuels
- 7) Weights may not extend beyond rear tires. All weights to be safely secured on brackets, or bolted solid, no weights on seat or operators platform
- 8) 100 lbs weight allowance for scale variance, all tractors must rescale after pulling.

## Heavy 11,500 & 13,500 Rules

**\*\*\*\* Any decision made the day of will supersede these posted rules.\*\*\*\***

**Hook fee will be \$20/hook, with a yearly \$10 insurance fee for each driver.**

1. No cut tires, if we can see they are cut (Grinder marks, hot knife marks, planer marks, etc) you will be disqualified.
2. Hitch; Hole size to be 3" wide x 3-3/4" long MINIMUM. Hook point to be a minimum of 18" back from the centerline of the rear axle, and a maximum of 20" high. This will be checked at the scale. If we cannot fit the hook in your hitch, you will not pull.
3. RPM's; Rpm's will be limited to a maximum of 3,000, if we feel you are in question, we do reserve the right to check you, denial to do so will result in DQ
4. Speed; Farm Stock will run at an 8.0 mph pace, 8.1 or higher will result in DQ. Enhanced Farm Stock will be 16.0 mph, 16.1 or higher will be a DQ
5. Safety Equipment; ALL ENHANCED TRACTORS MUST HAVE THE FOLLOWING

- a. Wheelie bars
- b. Guillotine Air shutoff with sled and driver hookups
- c. Helmets required for roll cage, highly recommended for roll bar

6. No weights may hang behind the rear tires, nor may they extend farther forward than 13' from the centerline of the rear axle. Wheel weights may not stick out past the axle. Weights may not obstruct the hookman from hooking/unhooking you from the sled, if they cannot safely hook you, we reserve the right to not allow you to pull.

7. Tires to be a maximum of 24.5 width

8. No injectables of any kind.

**Pulling order will be determined the night of the pull**

Contacts Jen Hartman 610-751-8031 / Chris Blatt 484-256-1755